





MODEL	MAGNUM 15	MAGNUM 20	MAGNUM 30
ENGINE	350-horsepower CAT <sup>®</sup> C9 ACERT (Tier 3)	440-horsepower CAT <sup>®</sup> C13 ACERT (Tier 3)	550-horsepower CAT <sup>®</sup> C15 ACERT (Tier 3)
PROCESSING CAPACITY	Up to 350 TPH	Up to 500 TPH	Up to 650 TPH
FEED OPENING	40 inches by 32 inches	56 inches by 32 inches	56 inches by 43 inches
ROTOR SIZES	40 inches by 43 inches	40 inches by 56 inches	52 inches by 56 inches
WEIGHT	86,000 pounds	95,000 pounds	112,000 pounds





## **FEATURES**

- The Magnum's on-board power source runs the complete operation as well as three auxiliary outlets.
- Standard hydraulic outriggers make for quick machine setup.
- The optional, patented Hydraset Hopper<sup>™</sup> simplifies the connection and removal of the hopper/feeder. An internal power pack allows just one operator to attach and detach the unit for transportation in minutes.
- The optional in-line discharge belt features a heightened discharge point that reaches 10 feet, 11 inches for higher stockpiling.

## IROCK 5531 CANAL ROAD, VALLEY VIEW, OH 44125

Phone: 866-240-0201 • Fax: 440-735-4974 • Email: sales@irockcrushers.com

www.irockcrushers.com